

A Survey on Progressive Packet Arrivals in DTNs Using Dynamic Allocation

¹G.KUMARASWAMY, ²E.CHITTIBABU

¹M.Tech (CSE), Department of Computer Science & Engineering, Malla Reddy College Of Engineering,

²Assistant Professor, Department of Computer Science & Engineering, Malla Reddy College of Engineering, Maisammaguda (v) I Dhulapally (M), Secunderabad.

Abstract: - Delay Tolerant Networks (DTNs), also called as intermittently connected mobile networks, are wireless networks in which a fully connected path from source to destination is unlikely to exist. However, effective forwarding based on a limited knowledge of contact behavior of nodes is challenging. When large files need to be transferred from source to destination make all the packets available at the source and transfer the file as small packets. We study the packets arrival at source and analysis their performance. We consider the linear blocks and rateless linear coding to generate redundancy and also for energy constraint .We scheduling the large file into small packets and delivering through multipath to destination, for this we use optimal user centric allocation and scheduling the packets in the receiver side.

Keywords – Delay tolerant networks, network coding, rate less codes

1. INTRODUCTION

Delay Tolerant Networks (DTNs), also called as Intermittently connected mobile networks, are wireless networks in which a fully connected path from source to destination is unlikely to exist. In these networks, for message delivery, nodes use store-carry-and-forward paradigm to route the messages. The examples of this networks are wildlife tracking, military networks etc. However, effective forwarding based on a limited knowledge of contact behavior of nodes is challenging. It becomes crucial to design efficient resource allocation and data storage protocols. Although the connectivity of nodes is not constantly maintained, it is still desirable to allow communication between nodes. Each time the source meets a relay node, it chooses a frame i for transmission with probability u_i . In the basic scenario, the source has initially all the packets .Under this assumption it was shown in [2] that the transmission policy has a threshold structure: it is optimal to use all opportunities to spread packets till some time σ depending on the energy

Constraint and then stop. This policy resembles the well-known "Spray-and-Wait" policy [3]. In this work we assume a more general arrival process of packets: they need to be simultaneously available for

transmission initially, i.e., when forwarding starts, as assumed in [2]. This is the case when large multimedia files are recorded at the source node that sends them out (in a DTN fashion) after waiting for the whole file reception. This paper focuses on general packet arrivals at the source and two-hop routing. We distinguish two cases: when the source can overwrite its own packets in the relay nodes, and when it cannot.

2. RELATED WORK

In forward error correction (FEC)[5]method Several satellites need to receive several data packets, that may need retransmission due to channel errors .Because many sites may need Retransmissions, the problem is to avoid the phenomenon of ACK implosion due to several sites requesting repairs .several works to combine FEC and acknowledgment-based retransmission protocols, such as [6].The effort there was to improve timeliness of packet delivery in multicasting multimedia streams which are subject to hard delay constraints. In DTNs the framework is different since the challenges are to overcome frequent disconnections. Papers [7] and [8] propose a technique to erasure code a file and distribute the generated code-blocks over a large number of relays

in DTNs, so as to increase the efficiency of DTNs under uncertain mobility patterns. In [8] the performance gain of the coding scheme is compared with simple replication. The benefit of coding is assessed by extensive simulations and for different routing protocols, including two hop routing.

3. THE MODEL

Consider a network that contains $N + 1$ mobile node. Two nodes are able to communicate when they come within reciprocal radio range and communications are bidirectional. We assume that the duration of such contacts is sufficient to exchange all frames: this let us consider nodes meeting times only, i.e., time instant when a pair of not connected nodes fall within reciprocal radio range. Time between contacts of pairs of nodes is exponentially distributed with given inter-meeting intensity [3]. A file contains K frames. The source of the file receives the frames at some times $t_1 \leq t_2 \leq \dots \leq t_K$. t_i are called the arrival times. The transmitted file is relevant during some time τ . By that we mean that all frames should arrive at the destination by time $t_1 + \tau$. We do not assume any feedback that allows the source or other mobiles to know whether the file has made it successfully to the destination within time τ . If at time t the source encounters a mobile which does not have any frame, it gives it frame i with probability $u_i(t)$. Consider two-hop routing. In this we used two concept overwrite case and non-overwriting case. In the existing concept non-overwriting case are highly efficient but overwriting case without constraints are not efficient, so in this work we use rate less code and block code for removing the overwriting case due to the transmission of packet.

4. ENERGY CONSTRAINTS

Denote by $E(t)$ the energy consumed by the whole network for transmitting and receiving a file during the time interval $[0, t]$. It is proportional to $X(t) - X(0)$ since we assume that the file is transmitted only to mobiles that do not

Have the file, and thus the number of transmissions of the file during $[0, t]$ plus the number of mobiles that had it at time zero equals to the number of mobiles that have it. Also, let $\xi > 0$ be the energy spent to forward a frame during a contact (notice that it includes also the energy spent to receive the file at the receiver side). We thus have $\xi(t) = \xi(X(t) - X(0))$.

5. CONCLUSION

Information is send to the destination after available of entire data at the source side. We use two concepts overwriting and non-overwriting cases non-overwriting case are highly efficient but overwriting case without constraints are not efficient, so we use rate less code and block code for removing the overwriting case for the transmission of packet. Rate less code and block code is used for share the information sequence to the receiver without data loss, overwriting and delay. For data transmission the multi path is created using optimal user centric algorithm in the source side. Using the multi path the data can split into packet and assign packet to each node for the transmission, then packet are schedule using decentralized routing process based on the integer linear programming in the receiver side in the scheduling packet the packet can schedule and receive to the client side. This process can used to efficiently send the data from source side to the destination side using delay tolerant network.

6. REFERENCES

- [1] E. Altman, F. De Pellegrini, and L. Sattelli, "Dynamic control of coding in delay tolerant networks," in Proc. 2010 IEEE INFOCOM
- [2] E. Altman and F. De Pellegrini, "Forward correction and Fountain codes in delay tolerant networks," in Proc. 2009 IEEE INFOCOM
- [3] T. Spyropoulos, K. Psounis, and C. Raghavendra, "Efficient routing in intermittently connected mobile networks: the multi-copy case," ACM/IEEE Trans. .
- [4] E. Altman, T. Basar, and F. De Pellegrini, "Optimal monotone forwarding policies in delay tolerant mobile ad-hoc networks," in Proc. 2008 ACM/ICST Inter-Perf.
- [5] J. Metzner, "An improved broadcast retransmission protocol," IEEE Trans. Commun.,
- [6] J. Nonnenmacher, E. Biersack, and D. Towsley, "Parity-based loss recovery for reliable multicast transmission," IEEE/ACM Trans. Netw.,
- [7] S. Jain, M. Demmer, R. Patra, and K. Fall, "Using redundancy to cope with failures in a delay tolerant network," SIGCOMM Comput. Commun.
- [8] Y. Wang, S. Jain, M. Martonosi, and K. Fall, "Erasure-coding based routing for opportunistic networks," in Proc. 2000